



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2017



Version number 13

Revision: 30.05.2017

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- **Trade name: KEIM ECOTEC**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture** Hydrophobing agent concentrate
- **Uses advised against** All other uses are not recommended.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
KEIM MINERAL PAINTS LTD  
Santok Building / Deer Park Way, Donnington Wood GB-Telford, Shropshire TF2 7NA  
Tel +44 1952 231 250 / Fax +44 1952 231 251  
www.keimpaints.co.uk / sales@keimpaints.co.uk
- **Further information obtainable from:**  
David Pratt  
Telefon: +44 1952 231250  
E-Mail: sales@keimpaints.co.uk
- **1.4 Emergency telephone number:**  
GBK GmbH Global Regulatory Compliance  
Emergency number: +49(0)6132/84463

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Flam. Liq. 3 H226 Flammable liquid and vapour.  
Eye Dam. 1 H318 Causes serious eye damage.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**  
  
GHS02 GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Polydimethylsiloxane with aminoalkyl groups  
Propionic acid
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H318 Causes serious eye damage.

(Contd. on page 2)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 1)

**Precautionary statements**

- P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe spray.  
P233 Keep container tightly closed.  
P243 Take action to prevent static discharges.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P315 Get immediate medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, sand, extinguishing powder.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

- **Description:** Alkylsilicone resin with alkoxy groups

**Dangerous components:**

CAS: 35435-21-3 EINECS: 252-558-1 Reg.nr.: 01-2119555666-27-XXXX	Alkyltriethoxysilane ⚠ Flam. Liq. 3, H226	50-100%
CAS: 67923-07-3 Polymer	Polydimethylsiloxane with aminoalkyl groups ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	10-20%
CAS: 79-09-4 EINECS: 201-176-3 Index number: 607-089-00-0 Reg.nr.: 01-2119486971-24	Propionic acid ⚠ Flam. Liq. 3, H226; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	< 5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:**

- When seeing the doctor we suggest to present this safety data sheet.
- Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 2)

- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Do not use solvents or thinners.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Rinse mouth and throat well with water.  
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Fire-extinguishing powder  
Alcohol resistant foam  
Carbon dioxide (CO<sub>2</sub>)
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
carbon oxide (CO<sub>x</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
silicon dioxid (SiO<sub>2</sub>)  
Nitrogen oxides
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** In case of fire do not breathe smoke, fumes and vapours.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Respect the protection rules (see section 7 a. 8).  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Keep away from ignition sources.  
Wear protective equipment. Keep unprotected persons away.  
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**  
Do not allow product to reach soil, sewage system or any water course.  
Follow local governmental rules and regulations.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.

(Contd. on page 4)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 3)

- Danger of slipping!
- Absorb with non-combustible liquid-binding material (sand, diatomite, vermiculite).
- Dispose of the material collected according to regulations.
- Clear contaminated areas thoroughly.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Avoid contact with skin and eyes.
  - Keep receptacles tightly sealed.
  - Ensure good ventilation/exhaustion at the workplace.
  - Do not inhale aerosols.
  - See item 8 for information about suitable protective equipment and technical precautions. Respect the protection rules.
- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Cool endangered receptacles with water spray.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Store only in unopened original receptacles.
  - Keep in the original containers in a cool and dry place.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
  - Store in a cool place.
  - Store in dry conditions.
  - Protect from frost.
  - Keep container tightly sealed.
  - Protect from heat and direct sunlight.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**79-09-4 Propionic acid**

WEL	Short-term value: 46 mg/m <sup>3</sup> , 15 ppm Long-term value: 31 mg/m <sup>3</sup> , 10 ppm
-----	---

(Contd. on page 5)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 4)

**· DNELs****35435-21-3 Alkyltriethoxysilane**

Oral	Long-term - systemic effects, consumer	9.5 mg/kg/day (consumer)
Dermal	Long-term - systemic effects, worker	13.4 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, consumer	9.5 mg/kg/day (consumer)
	Acute-systemic effects, worker	45 (worker)
	Acute-systemic effects, consumer	67.8 (consumer)
	Long-term - systemic effects, consumer	11.3 mg/m <sup>3</sup> (consumer)

**· PNECs****35435-21-3 Alkyltriethoxysilane**

Aquatic compartment - freshwater	0.64 mg/l (freshwater)
Aquatic compartment - marine water	0.064 mg/l (marine water)
Aquatic compartment - water, intermittent releases	6.4 mg/l (not specified)
Aquatic compartment - sediment in freshwater	4.3 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment in marine water	0.43 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	0.48 mg/kg dw (soil)
Sewage treatment plant	1 mg/l (sewage treatment plant)
Oral secondary poisoning	10 mg/kg food (not specified)

**· Additional information:** The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

- Avoid contact with the eyes and skin.
- Do not inhale gases / fumes / aerosols.
- Wash hands before breaks and at the end of work.
- Immediately remove all soiled and contaminated clothing

**· Respiratory protection:**

- Use suitable respiratory protective device only when aerosol or mist is formed.
- Combination filter A/P

**· Protection of hands:** Protective gloves**· Material of gloves**

- suitable material e.g.:
- Butyl rubber, BR
- Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

- Value for the permeation: Level  $\geq 3$  (60 min)

(Contd. on page 6)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 5)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Tightly sealed goggles
- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment** See Section 12 and 6.2

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

· <b>Form:</b>	Fluid
· <b>Colour:</b>	Yellowish
· <b>Odour:</b>	Weak, characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value at 20 °C:** 5-6\*

##### · Change in condition

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	Undetermined.

· **Flash point:** 25 °C (DIN 53213)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 265 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Explosion limits:

· <b>Lower:</b>	Not determined
· <b>Upper:</b>	Not determined

· **Vapour pressure:** Not determined.

· **Density at 25 °C:** 0.9-1.0\* g/cm<sup>3</sup> (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not applicable

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:** Fully miscible.

(Contd. on page 7)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 6)

- **Partition coefficient: n-octanol/water:** Not applicable
- **Viscosity:**
  - Dynamic at 25 °C:** 1-10\* mPas (DIN 51562)
  - Kinematic:** Not determined.
- **9.2 Other information**
  - \* The values are for freshly produced material and may change with the time.
  - Explosion limits for released ethanol: 3,5 - 15% (V).

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal conditions of storage and use.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**  
Reacts slowly with: Water. The reaction is the formation of: ethanol. This leads to a reduction of the flash point.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
In case of fire, the following can be released:  
carbon oxide (COx)  
Nitrogen oxides (NOx)  
silicon dioxide (SiO<sub>2</sub>)  
Nitrogen oxides  
No hazardous decomposition products if stored and handled as prescribed.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

Oral	LD50	> 2000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)

**35435-21-3 Alkyltriethoxysilane**

Oral	LD50	>2000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
	NOAEL	150 mg/kg (rat)

**79-09-4 Propionic acid**

Oral	LD50	2600 mg/kg (rat)
Dermal	LD50	500 mg/kg (rabbit)

(Contd. on page 8)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 7)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
not irritating on rabbit  
Frequent persistent contact with the skin may cause skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **during inhalation:** Irritant effect possible.
- **during swallowing:** Irritant effect possible
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**  
Experimental analysis are not available.  
The product was not tested. The statements on toxicology have been derived from the properties of the individual components.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** not applicable
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · **Aquatic toxicity:**

###### **35435-21-3 Alkyltriethoxysilane**

NOEC	(21d), 32 mg/l (daphnia) (reproduction)
EC 50/3h	>100 mg/l (sewage sludge)
LC 50/96 h	> 100 mg/l (fish) (OECD 203, semistatisch)

- **12.2 Persistence and degradability** Moderately /partly biodegradable
- **12.3 Bioaccumulative potential** Non significant accumulation in organisms
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **AOX-indication:**  
Due to the substance of content which do not include organic jointed halogens, the product can not take influence on the AOX-load of the waste water.
- **According to the formulation contains the following heavy metals and compounds from the EU guideline NO. 2006/11/EC:**  
According to our current data base the product does not consist of any heavy metals or substances of EU-directives 76/464/EWG.
- **General notes:**  
At present there are no ecotoxicological assessments.  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 9)





## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 8)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.

- **European waste catalogue**

07 01 99	wastes not otherwise specified
----------	--------------------------------

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary with cleansing agents.

### SECTION 14: Transport information

- |   |  |
|---|--|
| · <b>14.1 UN-Number</b><br>· <b>ADR, IMDG, IATA</b>   | UN1993   |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR</b><br>· <b>IMDG, IATA</b>  | 1993 FLAMMABLE LIQUID, N.O.S.<br>(Alkyltriethoxysilane), special provision 640E<br>FLAMMABLE LIQUID, N.O.S. (Alkyltriethoxysilane) |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, IMDG, IATA</b>  |  |
| <br>· <b>Class</b><br>· <b>Label</b> | 3 Flammable liquids.<br>3  |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | III  |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>  | No   |
| · <b>14.6 Special precautions for user</b><br>· <b>Danger code (Kemler):</b><br>· <b>EMS Number:</b>                    | Warning: Flammable liquids.<br>30<br>F-E,S-E   |

(Contd. on page 10)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 9)

· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640E (ALKYLTRIETHOXYSILANE), 3, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**  
For information on labelling please refer to section 2 of this document.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Other regulations, limitations and prohibitive regulations**
- **Please note:**  
TRGS 200 (Germany)  
TRGS 500 (Germany)  
TRGS 510 (Germany)  
TRGS 900 (Germany)
- **Substances of very high concern (SVHC) according to REACH, Article 57** not applicable

(Contd. on page 11)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2017

Version number 13

Revision: 30.05.2017

**Trade name: KEIM ECOTEC**

(Contd. of page 10)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.

- **Department issuing SDS:** KEIMFARBEN Germany, Product safety department

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- EC10: Effective concentration at 10% mortality rate.
- EC50: Half maximal effective concentration.
- LC10: Lethal concentration at 10% mortality rate.
- NOEC: No observed effect concentration.
- REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1

- \* **Data compared to the previous version altered.**